

## AH500T PCB TRANSPORTATION UNITS

THE CONVEYORS AH500T ARE DESIGNED FOR PCB TRANSPORTATION IN AUTOMATIC LINES AND FOR MACHINES INTERFACE FOR SMT AND TH. ARE AVAILABLE IN DIFFERENT LENGTHS, 1000, 1500, 2000 mm, WITH ADJUSTMENT (50 - 450 mm) WITH MOTOR, WHEEL OR FIX.



SMEMA INTERFACE, MANUAL SWITCH FOR WORK STATIONS AND INSPECTION.

ARE ALSO AVAILABLE MULTISTAGE UNITS 2-3-4 CONVEYORS WITH INDEPENDENT MOTORS, AS BUFFER FOR 2 OR MORE PCBs.

|   |        |   |          |   |       |   |            |
|---|--------|---|----------|---|-------|---|------------|
| A | 0.5 mt | 1 | 1 stage  | M | Motor | L | Left/Right |
| B | 1 mt   | 2 | 2 stages | V | Well  | R | Right/Left |
| C | 1.5 mt | 3 | 3 stages | F | Fix   | - | -          |
| D | -      | 4 | 4 stages | - | -     | - | -          |

ORDER EXAMPLE : AH500T/C/1/M/L

OTHER HANDLINGS:

LOADING/UNLOADING FOR PCB, BUFFER, INVERTER, COMPLETE AUTOMATION.